



Trakya Cam Sanayii A.Ş.  
Adres: İş Kuleleri Kule 3 34330  
4.Levent- İSTANBUL/TÜRKİYE  
06

EN 1096-4

On-line coated glass, intended to be used in buildings and construction works, 4mm Aura Reflekta

Characteristics

Resistance to fire	NPD
Reaction to fire	A1
External fire behaviour	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	NPD
Resistance against sudden temperature changes and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance of the glass unit	4mm
Direct airborne sound reduction	29 (-2; -3) dB
Thermal properties	
U-value (EN 673)	5,8 W/(m <sup>2</sup> K)
Normal emissivity (EN 12898)	0,89
Radiation properties	
Light transmission and reflection	0,34/0,51/0,44
Solar energy characteristics	0,45/0,37/0,31

NPD: No Performance Determined



Trakya Cam Sanayii A.Ş.  
Adres: İş Kuleleri Kule 3 34330  
4.Levent- İSTANBUL/TÜRKİYE  
06

#### EN 1096-4

On-line coated glass, intended to be used in buildings and construction works, 6mm Aura Reflekta

#### Characteristics

Resistance to fire	NPD
Reaction to fire	A1
External fire behaviour	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	NPD
Resistance against sudden temperature changes and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance of the glass unit	6mm
Direct airborne sound reduction	31 (-2; -3) dB
Thermal properties	
U-value (EN 673)	5,7 W/(m <sup>2</sup> K)
Normal emissivity (EN 12898)	0,89
Radiation properties	
Light transmission and reflection	0,34/0,50/0,43
Solar energy characteristics	0,43/0,36/0,28

NPD: No Performance Determined